


TECHNICAL SPECIFICATIONS

	SE 360 DL	SE 400 DL	SE 440 DL	SE 490 DL
Overall length	3.60 m / 11'10"	4.00 m / 13'1"	4.40 m / 14'5"	4.90 m / 16'1"
Overall beam	1.77 m / 5'10"	1.77 m / 5'10"	1.86 m / 6'1"	2.05 m / 6'9"
Inside Length	2.00 m / 6'7"	2.40 m / 7'10"	2.80 m / 9'2"	2.98 m / 9'9"
Inside beam	0.86 m / 2'10"	0.86 m / 2'10"	0.94 m / 3'1"	1.05 m / 3'5"
Dry weight (estimate)**	200 kg / 441 lbs	218 kg / 481 lbs	273 kg / 602 lbs	390 kg / 860 lbs
Tube diameter	0.45 m / 1'6"	0.45 m / 1'6"	0.45 m / 1'6"	0.50 m / 1'8"
Fabric type	CR / CSM (1100 dtx)			
Number of chambers	3	3	3	5
Maximum payload**	605 kg /1334 lbs	735 kg /1620 lbs	850 kg /1874 lbs	945 kg /2083 lbs
Passenger capacity (category C)	4	5	6	9
Design Category (European Directive No 94/25/CE)	C			
Shaft length	Long			
Maximum power**	40 hp	50 hp	60 hp	90 hp
Maximum engine weight**	100 kg / 220 lbs	110 kg / 243 lbs	120 kg / 265 lbs	170 kg / 375 lbs
Fuel tank capacity	35 L	35 L	57 L	85 L

** Homologation pending

OPTIONAL ACCESSORIES

Lifting sling kit	Ski pole (490 DL) / Turboswing
Bathing ladder	Synthetic teak deck
Back rests (pilot / co-pilot)	Windshield

Z Nautic reserves the right to modify the characteristics of its products without warning (dimensions and weight +/- 3%).

STANDARD FEATURES

HULL

- V-shaped fiberglass hull with built-in flaps (deep V on 490)
- Moulded non-skid deck
- Anchor locker with upholstered seat
- Rear locker with gas strut
- Lateral locker (440/490)
- 1 bow D-ring
- 2 stern rings
- 1 self-bailer



BUOYANCY TUBE

- CR/CSM fabric (1100 dtx)
- Choice of tube set colour (medium grey/marine blue /camel)
- Removable tube system
- Semi-recessed Easy Push valves
- Large profile rubstrake
- Reinforced cone ends
- Interior handles (6 on 360, 8 on 400/440/490)

STANDARD EQUIPMENT

- Low profile fiberglass bow boarding step, including synthetic teak
- Stern boarding steps, including synthetic teak
- Steering console with:
 - Steering wheel + steering system + cable
 - 3 breakers
 - Glove box
- Built-in fuel tank + gauge + fuel/water separator
 - 35 litres / 9.2 US gal (360/400)
 - 57 litres / 15 US gal (440)
 - 85 litres/ 22.5 US gal (490)
- Recess for extinguisher
- Double pilot/co-pilot seat with removable upholstered seat
- Passenger seats with removable upholstered cushion
- 3 stainless steel mooring cleats
- 3 lifting points
- Courtesy light
- Navigation lights
- 12-volt plug (490)
- Battery switch
- Battery box
- Automatic bilge pump
- 2 paddles
- Foot pump
- Pressure gauge
- Repair kit
- Owner's manual

